Quick Ø35

WORKTOP CONNECTORS





SYMBOLS



= SHELF SAFELY LOCKED DURING TRANSPORTATION AND AT HOME.



= ANTI-TURNOVER LOCKING SYSTEM



NOTE: Printing errors and omissions may exist despite our best efforts to ensure accurancy. We reserve the right to alter specifications without notice.

MATERIALS



OTHER FINISHES AVAILABLE

ON REQUEST

=

+

FINISHES

PART NO.	FINISHES	PART NO.	FINISHES	PART NO.	FINISHES
00	Insignificant finish	IF	Middle Grey	RO	Red
AA	Natural	IJ	Light Grey	UT	T-Met 9007
AB	White	IL	Grey 20	UZ	T-Met
AE	White 9010	IN	Grey met. 26	WA	Bronzed
EA	Black	JB	Bright Aluminium	wi	Burnished
EC	Matt Black	JC	Aluminium - Chrome	XD	Satin-finished Steel
EE	Anthracite	JD	Matt Aluminium	YA	Nickel-plated
EW	Grey 9007	JE	Satin-finished Aluminium	YB	Bright Nickel-plated
FU	Gunmetal	JF	Aluminium - Brass	YC	Matt Nickel-plated
FV	Gunmetal V52	JG	Aluminium 5	YD	Satin-finished Nickel-plated
GR	Raw	JL	Aluminium PE 11	YQ	Black Nickel
НА	Brass-Plated	JM	Aluminium RAL 9006	Z9	Black Zinc
нн	Tropicalized	КА	Chrome	ZA	Zinc alloy
HL	Raw Brass	КВ	Bright Chrome	ZN	Zinc-plated
нх	Graphite	кс	Matt Chrome	ZQ	Bright Gold
IA	Grey	LD	Brown 8019	ZY	Titanum
IB	Metallic Grey	NN	Metallic Beige	ZZ	Clear





QUICK

WORKTOP

CONNECTORS



QUICK Ø35 has been conceived to join two worktops or panels together.

It consists of two parts:

- main body with tightening dowel M8x64, M8x100 or M8x150; - round cap to suit the dowel head. The installation is fast and simple as the two parts don't fall

when placed in position.

The fastening becomes easier by using an S6 mm allen wrench, or even better, a cordless driver.

It is suitable for worktops and panels minimum 25 mm thick. The tightening is 6 mm.







QUICK Ø 35



























= Ø 35 mm	
EP) = 500 pcs.
2162001000	



QUICK Ø 35



DRILL BIT FOR QUICK Ø 35 mm











HSS	\bigcirc = on request
1621454000	





www.italianaferramenta.it